

DUPONT™ STONETECH® PROFESSIONAL SEMI GLOSS FINISHING SEALER

TECHNICAL DATA SHEET



PRODUCT BENEFITS

- Two-in-one formula leaves a light sheen and protects against stains
- Interior use
- Easy to use, water-based formula

RECOMMENDED SURFACES

Slate, saltillo, and concrete floors. Not intended for use on glazed, polished, honed or non-absorbing surfaces, wood floors and decks, showers, countertops, and near pool areas.

AVAILABLE SIZES

Quart, Gallon

COVERAGE

Up to 300 sq ft per gallon, depending on porosity of surface.

EXPECTED WEAR

Up to 5 years. Touch up on higher traffic areas may be required on a more frequent basis.

TECHNICAL INFORMATION

Form:	Liquid
Specific Gravity:	1.01
HMIS Rating:	2,1,0
Flash Point:	>200 °F (93.3 °C)
Freeze Point:	32 °F (0 °C)
pH:	8.70

VOC CONTENT

<50 g/L

LEED points qualified product.

DIRECTIONS

Read entire label before using. Use only as directed. Always test in a small inconspicuous area to determine appropriate application method, achievement of desired results, and to ensure good adhesion. Ensure work area is well-ventilated during application and until surface is dry. Keep children and pets out of the area until the treated surface is dry. Avoid applying product in direct sunlight. Surface temperature should be 50 °F–80 °F (10 °C–27 °C). Surface must be thoroughly clean, dry, and free of any sealers or coatings before application. Application to a dirty or dusty surface will affect adhesion and appearance. Semi Gloss Finishing Sealer should not be applied to a wet or moist surface. Avoid applying onto surfaces not intended for treatment. For new installations, sealer can be applied as soon as 48–72 hours after grouting. Fresh concrete slabs require a minimum of 28 days to cure before applying the sealer.

1. SHAKE WELL BEFORE USING. Do not dilute before applying.
2. Liberally apply 1–3 even coats with a natural bristle paint brush, paint roller, low pressure sprayer, or pump-up garden sprayer. Avoid puddling of product during application.
3. Allow 30–45 minutes between coats or until surface is dry.
4. Surface traffic may begin 12 hours after final application; keep installation dry for a minimum of 12 hours; full cure is achieved in 24–48 hours.
5. Keep surface clean and dry as finished surfaces may become slippery when wet.
6. Clean tools used during application with water.

STORAGE AND HANDLING INSTRUCTIONS

CAUTION: MAY CAUSE RESPIRATORY IRRITATION. Do not ingest. Avoid prolonged exposure to vapors. Use in a well-ventilated area. For repeated or professional use, an approved respirator and gloves are recommended. Consult MSDS. KEEP OUT OF THE REACH OF CHILDREN. Do not freeze or store above 100 °F/38 °C. Do not mix with other chemicals. Do not release to natural waterways.

EMERGENCY/FIRST AID PROCEDURES

Ingestion: Do not induce vomiting. Call poison control center. Call a physician immediately.

Eye Contact: Flush thoroughly with water for at least 15 minutes. Call a physician if eye irritation persists.

Skin Contact: Wash skin with mild soap and water. Call a physician if skin irritation persists. Launder affected clothing before re-wearing.

Inhalation: Remove affected person to fresh air. Call a physician if respiratory irritation persists.

The DuPont™ StoneTech® Professional product line complies with all federal, state and local VOC regulatory requirements.

DuPont™ StoneTech® Professional
2520 Barrington Court
Hayward, CA 94545

Technical Support: 888-786-6343
Customer Service: 877-786-6383

www.stonetechpro.com



The miracles of science™

The information is furnished free of charge and based on information that DuPont believes to be generally reliable and accurate. Individual facts and circumstances may differ. It is intended for your use at your own risk. Because conditions of use are outside our control, we make no warranties, express or implied, and assume no liability in connection with any use of this information.

Copyright © 2014 DuPont. The DuPont Oval Logo, DuPont®, The miracles of science®, and StoneTech® are registered trademarks or trademarks of E.I. du Pont de Nemours and Company or its affiliates. All rights reserved.

K-20520-2 (03/14)