



Husqvarna K 1260 Rail

Cutting a rail track takes power, precision and speed. The K 1260 Rail is the market's most powerful cutter, customized for railways, tram tracks and metro systems. It cuts fast and straight, the attachment mounts quickly to the rail and the double attachment mountings allow you to cut from any direction.



PERFECT RIGHT-ANGLE CUTS

The RA 10 attachment fastens to the track to ensure a perfect right-angle cut.



CUTTING FROM BOTH SIDES

The RA 10 attachment is included as standard and allows cutting from both sides of the track.



FAST, STABLE MOUNTING

Fast, stable mounting of the attachment onto the track.



HIGH POWER WITH LESS FUEL

Our built-in automatic filter compensation SmartCarb™ maintains high power and lowers fuel consumption.

Features Husqvarna K 1260 Rail

- Reduced wear thanks to the drive belt with fully sealed transmission, which keeps out the cutting dust.
- The only time the filter needs to be checked and changed is if you experience lack of power.
- Our two-step filtration system with centrifugal cleaning and a single paper filter increases product life and extends service intervals.
- Our anti-vibration system reduces vibrations in the cutter handles, so they are more comfortable to hold and can be used for longer periods. To provide the user a comfortable operating position and to reduce strain, the distance between the handles is large. The handles and the short engine body mean the user always stands close to the machine, for easier handling and control.
- EasyStart ensures easier starting by reducing the compression in the cylinder.
- Our built-in automatic filter compensation maintains high power during the air filter life time.
- Provides better transmission of power, less frequent re-tensioning and extended service intervals.
- The water adjustment gives efficient dust management and makes operation easier and more efficient.

TECHNICAL SPECIFICATION	
Engine	Air-cooled 2 stroke engine
Cylinder displacement	7.25 cu.inch
Power output	7.9 hp
Fuel tank volume	42.3 fl oz
Idling speed	2700 rpm
Vibrations front handle	5/5 m/s ²
Vibrations rear handle	4.1/3.6 m/s ²
Sound pressure level at operators ear	103 dB(A)
Sound power level, guaranteed (LWA)	117 dB(A)
Blade diameter	14/16 "
Max cutting depth	5/6 "
Weight (excl. cutting equipment)	45.2/46.5 lbs

