



Husqvarna PG 530

PG 530 is a concrete floor grinder available in both 1- and 3-phase versions with high capacity. Its grinding width of 530 mm means it is excellent for residential and light commercial purposes. PG 530 combines the latest technology to deliver more power and performance than any other triple head planetary machine available in its class. Excellent choice for concrete floor preparation and repair as well as all polishing and grinding applications - both wet and dry. Perfect for HiPERFLOOR® concrete floor polishing system.



HIGH PRODUCTION RATE
High power machinery capable of delivering high production rates, increasing profit and saving valuable time.



STABLE OPERATION OVER UNDULATING SURFACES
The triple-headed grinder delivers more downward pressure and power to the grinding heads.



GEAR-DRIVEN PLANETARY HEAD
Gear-driven planetary head; premium quality belt for powering grinding heads.



TIME SAVING TOOL CHANGE
Redi Lock® is an instant and hassle-free system for changing diamond tooling.

Features Husqvarna PG 530

- Adjustable handlebar makes the setting of an ergonomic position easy.
- Thanks to the 5-way sealing mechanism, the spring steel head system and all zinc plated steel parts, service is not needed as often.
- Robust steel frame and strong single-piece aluminium cover.
- Enhanced operator control. FWD / REV operation with variable speed control.
- Redi Lock® is an instant and hassle-free system for changing diamond tooling. Robust system design ensures maximum protection and life of your diamond tools.

TECHNICAL SPECIFICATION	
Power output	5 hp
Rated current, A	16 A
Voltage	220/480V
Phases	3
Grinding width	21"
Grinding disc	9.5"
Grinding pressure total	295 lbs
Grinding disc speed	200-1000 rpm
Planetary head speed	10-60 rpm
Direction of rotation	FWD/REV with grinding discs and planetary head rotation in same direction (not counter rotation).
Weight	475 lbs
Vibrations left handle	4.8 m/s ²
Vibrations right handle	2.7 m/s ²

