



Husqvarna Tilematic® TS 250 X3

The contractor's choice for production sawing and the chosen preference for the rental market, the Husqvarna Tilematic TS 250 X3 delivers more power with its high torque 1-1/2 hp motor. Rip cut up to 24" tiles or diagonally cut up to 18" tiles. Strength and durability are provided by the sliding water pan that is available in galvanized metal or stainless steel.

Shown with optional rolling stand. Galvanized pan shown.

Features Husqvarna Tilematic® TS 250 X3

- The cutting head can be adjusted to various heights
- Smooth rolling, large conveyor carts with metal wheels maintain high precision with fewer parts and less wear
- Patented sliding tray design allows maximum cutting capacity on large tiles.
- The adjustable rolling stand has a patent-pending spring-assist for easy raising/lowering of saw.
- A large 18" x 16-1/2" conveyor cart better supports larger tile.
- Features a 1-1/2 hp Baldor single voltage continuous-duty motor that is a totally enclosed fan cooled (T.E.F.C.) and designed exclusively for Husqvarna.
- Choose rust-resistant galvanized pan or rust-proof stainless steel for easiest cleaning and maintenance.
- Bladeshaft lock makes blade removal easier.
- Make spring-assisted plunge cuts.
- Motor is high torque for production sawing capability and is both UL and CSA rated.
- Utilizes dual capacitors for increased power efficiency in low voltage starting conditions.
- Saws feature a sliding pan for operator's convenience.
- Premium, 6-groove poly V-belt are smoother running with less vibration, reducing belt slippage and transmitting more power to the bladeshaft.
- Three holes on support arm allow for fast, easy adjustment for different size blades (6", 8", and 10").

TECHNICAL SPECIFICATION	
Power output	1.5 hp
Motor manufacturer	Baldor
Voltage	115V
Voltage	EU 115V/UK 0V/US 0V/JP 0V/OTHER 0V
Amperage	EU 14.4A/UK 0A/US 0A/JP 0A/OTHER 0A
Rated current, A	14.4A
Phases	1
Current phase cycle	60Hz
Blade shaft RPM	2760 rpm
Spindle diameter	0.625"
Blade diameter	10 inch
Max cutting depth	3.75 inch
Max cutting length	24 inch
Max tile size for diagonal cutting	18"
Cutting head	Cast aluminum, poly V-belt drive; swing away blade guard for easy blade mount
Water pan	Galvanized or stainless steel
Product size, LxWxH	39.125x25x21.75 inch
Weight	105 lbs
Weight incl. packaging	116 lbs

