



STONETECH® Oil Stain Remover

DS 214.0-0516

**Globally Proven
Construction Solutions**



1. PRODUCT NAME

STONETECH® Oil Stain Remover

2. MANUFACTURER

LATICRETE International, Inc.
1 LATICRETE Park North
Bethany, CT 06524-3423 USA

Telephone: +1.203.393.0010

Toll Free: +1.888.786.6343

Fax: +1.203.393.1684

Website: www.laticrete.com

3. PRODUCT DESCRIPTION

STONETECH Oil Stain Remover is designed to remove oil-based stains without discoloring the surface.

Uses (Interior and Exterior)

- Countertops
- Floors

Advantages

- Pulls out deep-set oil stains
- Leaves no permanent residue
- Easy to use
- Will not discolor stone

Recommended Surfaces

Natural stone, masonry and cementitious grout such as:

- Marble
- Granite
- Limestone
- Travertine
- Slate
- Sandstone
- Concrete
- Quartzite

Item Numbers and Packaging

D12446896 – 3oz (88.7mL) Can, 6 units per Case, 300 units per Pallet

D12446904– 1 Pint/16oz (473mL), 6 units per Case, 300 units per Pallet

Products Available for Sale in Canada Only:

D12752546- 3oz (88.7mL) Can, 6 units per Case, 300 units per Pallet

Approximate Coverage

- ½-1 ft² (0.05 – 0.09 m²) of surface at ¼" (6mm) thickness per pint (473 mL).
- 15-30 in² (97-194 cm²) of surface at ¼" (6mm) thickness per 3oz. can (473 mL).

Shelf Life

Factory sealed containers of this product are guaranteed to be of first quality for two (2) years if stored at temperatures >50°F (10°C) and <90°F (32°C).

VOC Content

Not Regulated

Cautions

Consult SDS for more safety information.

- Inhalation: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Get medical attention if any discomfort continues.
- Skin contact: Take off immediately all contaminated clothing. Wash contaminated clothing before reuse. If skin rash or an allergic skin reaction develops, get medical attention.
- Eye contact: Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention.
- Ingestion: Rinse mouth. Do not induce vomiting. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs. Get medical attention if any discomfort continues.

Storage and Handling Instructions

COMBUSTIBLE. HARMFUL IF SWALLOWED. Do not ingest. Avoid prolonged exposure to vapors. Use only in a well-ventilated area. MAY CAUSE EYE, SKIN AND RESPIRATORY IRRITATION. Avoid contact with eyes and skin. Wear solvent resistant gloves such as nitrile gloves. KEEP OUT OF THE REACH OF CHILDREN. Do not store above 100 °F (38 °C). Do not mix with other chemicals. Do not release to natural waterways.

4. TECHNICAL DATA

Physical Properties

Form	Paste
Color	Grey
Odor	Lemon

5. INSTALLATION

Surface Preparation

Read entire label before using. Use only as directed. Always test in a small inconspicuous area to determine that the desired results will be achieved. Make sure surface is clean, dry, and free of waxes and coatings. Ensure that area is well-ventilated and keep children and pets away from the area during application and until surface is clean and dry.

Directions

1. Using a plastic or wood spatula, stir thoroughly to mix the paste.
2. Apply a 1/4" (6mm) thick layer of paste to the stain. Ensure that the paste extends at least 1–2" (25-50mm) beyond the edge of the stain.
3. Do not cover.
4. Allow 48–72 hours for paste to completely dry.
5. Using a plastic spatula, remove dried product and discard.
6. Allow solvent to completely dry from the stone.
7. If stain is not completely gone after drying, repeat process.
8. Clean up residue and tools with mineral spirits.
9. Once the surface is dry, reseal the cleaned area with a STONETECH Sealer (e.g. STONETECH® BulletProof®).

6. AVAILABILITY AND COST

Availability

LATICRETE®, STONETECH and LATAPOXY® materials are available worldwide.

For Distributor Information, Call:

Toll Free: +1.888.786.6343

Telephone: +1.203.393.0010

For on-line distributor information, visit LATICRETE at www.stonetech.com or www.laticrete.com

Cost

Contact a LATICRETE Distributor in your area.

7. WARRANTY

See 10. FILING SYSTEM:

DS 230.13: LATICRETE Product Warranty

8. MAINTENANCE

Highly alkaline, acidic, ammoniated, and/or abrasive cleaners are not necessary for daily maintenance and may also degrade the sealer, adversely affecting stain resistance. Tile and stone routine cleaning with a neutral pH cleaner such as STONETECH Stone & Tile Cleaner is recommended. For tough or difficult to remove soil use STONETECH KlenzAll™ Cleaner, a nylon scrubbing pad or a long handled stiff bristle brush. Please note: Prior to using any cleaning material on a tile, stone, etc. installation, test a discrete area or scrap piece of tile to insure desired results. For additional information, please refer to the TDS 262 Stone and Tile Care Guide.

9. TECHNICAL SERVICES

Technical Assistance

Information is available by calling the LATICRETE Technical Service Hotline:

Toll Free: +1.888.786.6343, ext. 2

Telephone: +1.203.393.0010, ext. 235

Fax: +1.203.393.1948

Technical and Safety Literature

To acquire technical and safety literature, please visit our website at www.laticrete.com or www.stonetech.com.

10. FILING SYSTEM

Additional product information is available on our website at www.stonetech.com. The following is a list of related documents:

- DS 230.13: LATICRETE Product Warranty
- DS 211.0: STONETECH Stone & Tile Cleaner
- DS 215.0: STONETECH KlenzAll Cleaner
- TDS 262: Stone and Tile Care Guide
- DS 282.0: STONETECH Bulletproof