

511 Anti-Slip Formula

Slip Protection For

■ Granite	■ Marble	■ Limestone
■ Travertine	■ Natural Stone	■ Concrete
■ Ceramic Tile	■ Grout	■ Glazed Tile
■ Porcelain Tile	■ Slate	■ Terrazzo
■ Quarry Tile		

Uses

■ Kitchens	■ Bathrooms	■ Showers
■ Health	■ Driveways	■ Patios
■ Garages	■ Restaurants	■ Hotels
■ Commercial Buildings		

511 Anti-Slip is a professional grade penetrating sealer designed for the slip-protection of all ceramic tile, porcelain tile, polished marble, polished granite, concrete, masonry and other acid sensitive surfaces. **511 Anti-Slip** forms an invisible barrier that increases static coefficient of friction of whatever it is applied to while also offering resistance to moisture and stains and allowing total vapor to escape. **511 Anti-Slip** is not a surface coating and will not alter the natural look. All surfaces treated are harder and less slippery. **511 Anti-Slip** can be used on interior and exterior applications.

Re-application is necessary every 3 - 12 months depending on the surface and the location with respect to day to day traffic and wear and tear of the flooring surface.

Walking is the transfer of body weight from one foot to another. If the person walking weighs 160 lbs. then for a few seconds that foot is on the tile, you are placing that amount of weight onto the surface. Fingers or an empty shoe cannot duplicate the weight transfer and does not give a satisfactory result.

Special Features:

■ Interior & Exterior Use	■ Slip Resistant	■ Stain Resistant
■ Easy to Use	■ Retains Natural Color and Look	
■ Weather Resistant	■ One Product = Multiple Uses	
■ Easy-to-Use	■ OK for Food Areas	

Test Data

Laboratory tests for **511 Anti-Slip** are available upon request.

Sample Testing

Due to the variations between substrates, sample testing is recommended to assure maximum performance and suitability for the intended use. Several inconspicuous test patches should be completed. Minimal shading may occur. User must determine the suitability of the product for their intended use.

Important: Read entire label and SDS/PDS before using at miraclesealants.com. Use directly from container. Do NOT – under any circumstances – thin or dilute. Protect exposed surfaces including wood, carpet, metal & landscaping. Use Miracle Sealants Cleaning Products to assure the surface is clean and prepared for application and ongoing care and maintenance.

DIRECTIONS

- 1) Apply **511 Anti-Slip** evenly to surface until damp using a Miracle Sealants Applicator, clean white towel, micro fiber, paint roller or paint type brush.
- 2) Leave on the surface for 3 - 5 minutes for maximum penetration before removing all excess product with a clean white towel, micro fiber or carpet bonnet before it dries. Any excess product “residue” that dries on the surface can be removed by re-applying **511 Anti-Slip**, wetting the surface and immediately wiping off excess immediately while wet. A second application is necessary allow at least 2 - 4 hours before applying. Allow 24 - 72 hours to fully cure.
- 3) Re-application is necessary every 6 - 12 months depending on the surface and the location with respect to day to day foot traffic and wear and tear on the flooring surface.

For maximum stain protection apply one of **Miracle's Impregnator/ Penetrating Sealers** before applying **511 Anti-Slip**.

511 Anti-Slip is suitable for use on natural stone surfaces both interior and exterior.

Coverage

Coverage will vary depending on the substrate and the application techniques. Under normal conditions **511 Anti-Slip** should cover approximately 100 – 750 square feet per quart (9 – 68 square meters per 946 ml.)

Caution

Contains combustible petroleum distillates. Potentially toxic. Use in a well-ventilated area. Keep away from heat and open flames. Avoid inhalation and prolonged contact with skin. Gloves must be worn at all times. Store in upright position and do not allow to freeze. KEEP OUT OF REACH OF CHILDREN AND PETS.

Suggested First Aid

Eye Contact: Immediately flush eyes with plenty of water for at least 15 minutes. Get medical attention if irritation persists. **Swallowed:** Do not induce vomiting. Get medical attention. Never give anything by mouth to an unconscious person. **Skin Contact:** Wash with soap and water. Get medical attention if irritation persists. **Inhalation:** Remove to fresh air. If breathing is difficult, give oxygen. If not breathing, give artificial respiration. Seek medical attention.

If product is damaged during transportation contact Info Trac at (800) 535-5053

Warranty

Satisfaction guaranteed up to 20 years from the date of original purchase. For complete warranty information visit miraclesealants.com or call 800-350-1901 for assistance.

WARRANTY & CAUTIONS

Warranty

Instructions are a condensed guide and should not be considered complete. In the event of failure, the only obligation of Miracle Sealants Company shall be to replace such products proven to be defective. **Before using, user shall determine the suitability of the product for their intended use. User assumes all risks and liability whatsoever in connection therein.** Neither seller nor manufacturer shall be liable for any injury or inability to use this product.

Caution

Contains combustible petroleum distillates. Potentially toxic. Use in a well-ventilated area. Keep away from heat and open flames. Avoid inhalation and prolonged contact with skin. Gloves must be worn at all times. Store in upright position and do not allow to freeze. KEEP OUT OF REACH OF CHILDREN AND PETS.