

New PSC-600

HIGH-PERFORMANCE PNEUMATIC CUTTER

Newly Developed Motor Produces More Power

8.500 RPM

Composite End Case to Prevent Freezing Hands

Lightweight **For Better** Maneuverability

6" (150mm)

Blade Capacity



Combined **power** and comfort for the best results

SPECIFICATIONS

Model PS Air Pressure 85 PSI (Air Consumption 15 CFM (425) Weight 2.9 lbs (1. No Load Speed 8,500 Air Inlet 1/4" Water Inlet 1/8" Arbor. 7/8" (2 Max. Cutting Disc Diameter 6" (15)	6 Bar) L/min) 3 kgs) 0 RPM BSPP BSPP 2mm) 00mm)
Max. Cutting Disc Diameter 6" (15 Length	

EQUIPMENT INCLUDED

Air Hose (15ft / 4.5m) Water Hose (15ft / 4.5m) Side Handle (reversible) Rust Inhibitor Oil (6.7oz / 200ml) Screw (w/ O-Ring Seal for Oil Port) Exhaust Hose with Clamp Spring Washer 6" Safety Guard Double End Wrench (19mm / 22mm) Phillips Screwdriver Water Quick Coupler w/ Shut Off Valve O-Ring (O-Ring for Water Valve Repair) Single Open Wrench (22mm) Hex Wrench (6mm) Inner Flange for Cutting Outer Flange L-Bracket Inner Flange for Grinding




Center Water-Feed System to Deliver Ample Water **Regardless of Position**



Spring Return Throttle to

Avoid Accidental Start



Alpha Professional Tools®

15ft. All-Weather Hoses with Flexibility Down To -40°F Or +140°F (-40°C To +60°C)

103 Bauer Drive, Oakland, NJ 07436 • 800-648-7229 • Fax: 800-286-0114 www.alpha-tools.com