



# Blaze™

## URETHANE GROUT HAZE CLEANER

### KEY FEATURES

- Effectively removes urethane grout haze
- Easy application
- Compatible with all tile surfaces

### DESCRIPTION

Bostik Blaze™ Urethane Grout Haze Remover is an effective way to clean tile surfaces after installing urethane based grouts. It can be used to remove haze which may remain after urethane grout installation.

While urethane grout is typically easy to clean off the surface of most tiles, some surfaces create challenges that make it necessary to use a chemical-based cleaner to remove residual urethane film or haze. Surfaces that are more difficult to clean that will benefit from the use of Blaze™, include high gloss surfaces, through-body porcelains and etched/frosted glass.

### WHERE TO USE

Blaze™ is safe to use on ceramic and porcelain tile, natural stone such as granite, limestone, travertine, sandstone, flagstone, masonry, concrete, metal and glass tile. Test on natural stone first to ensure it does not etch the tile.

### DIRECTIONS FOR USE

Read and understand technical and safety data sheets completely before beginning installation. Refer to [www.bostik-us.com](http://www.bostik-us.com) for the most recent product information and safety data sheet prior to installation.

### APPLICATION

1. Follow all written installation instructions when applying urethane grout. For best results, remove urethane haze as you work by wiping the tile with a sponge, particularly in warm or dry climates. Refer to the appropriate urethane grout technical data sheet for complete instructions.
2. If haze cannot be removed with an alcohol based window cleaner such as Windex® use Blaze™. Wait 3 hours in low humidity/warm temperature (<50% RH and >70°F/21.1°C) environments; 6 hours in high humidity environments/cool temperature (>50% RH and <70°F/21.1°C) environments.
3. Spray Blaze™ on a scrub pad designed for delicate surfaces such as the 3M™ Doodlebug™ white cleaning pad.
4. Allow Blaze™ to rest on the tile/stone surface for at least 2 minutes to ensure sufficient penetration.



5. Rub the cleaning pad lightly over the urethane haze on the tile being careful not to touch the grout joints. Note that excessive haze may require direct spray on surface, more dwell time or repeated cleaning. Do not flood the surface with cleaner.
6. Use a damp sponge and clean water to remove the film and cleaner.
7. Finish by drying the tile surface with a clean towel or cloth.

It is not recommended to grout or clean tile if the tile surface temperature is above 90°F (32°C). If this is the case, wait for the tile surface to cool prior to grouting or cleaning. You can accelerate the tile cooling process by wiping with a damp sponge. Be careful not to add excessive water during the tile cooling process.

### COVERAGE

Blaze™ will cover approximately 350–400 sq. ft. per 24-oz. spray bottle and approximately 1,600–2,100 sq. ft. per 1-gallon bottle, depending upon spray pattern and installation conditions.

## LIMITATIONS

- Do not pour directly on grout.
- Do not mix with grout wash water.
- Always use protective clothing (gloves and eye protection) when working with urethane grout. For more information, consult the SDS for this product.
- Always test a small, inconspicuous area first to ensure compatibility with all surface types, including all adjacent surfaces.
- Using Blaze™ too soon in poor drying conditions (>50% RH and <70°F/21.1°C) may require minor repair of any grout damaged in the process of scrubbing away haze.
- Do not allow product to come in contact with any non-recommended surface.
- Take special care to avoid contact with painted surfaces.
- Contact Bostik Technical Services if persistent haze exists.
- Do not freeze or store above 100°F (38°C).

## PACKAGING

- 4 x 1 gal./case
- 12 x 24 oz./case

## WARNING

HARMFUL IF SWALLOWED. MAY CAUSE SEVERE EYE, SKIN AND RESPIRATORY IRRITATION.

## STORAGE/SHELF LIFE

Store in a clean, dry area, off the ground on a pallet, not affected by freezing or hot temperatures. Shelf life is one year from date of manufacturing in unopened container.

## LIMITED WARRANTY

Limited Warranty found at [www.bostik-us.com](http://www.bostik-us.com) or call 800.726.7845. TO THE MAXIMUM EXTENT ALLOWED BY LAW, BOSTIK DISCLAIMS ALL OTHER EXPRESS OR IMPLIED WARRANTIES, INCLUDING WITHOUT LIMITATION WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. UNLESS OTHERWISE STATED IN THE LIMITED WARRANTY, THE SOLE REMEDY FOR BREACH OF WARRANTY IS REPLACEMENT OF THE PRODUCT OR REFUND OF THE BUYER'S PURCHASE PRICE. BOSTIK DISCLAIMS ANY LIABILITY FOR DIRECT, INCIDENTAL, CONSEQUENTIAL, OR SPECIAL DAMAGES TO THE MAXIMUM EXTENT ALLOWED BY LAW. DISCLAIMERS OF IMPLIED WARRANTIES MAY NOT BE APPLICABLE TO CERTAIN CLASSES OF BUYERS AND SOME STATES DO NOT ALLOW THE EXCLUSION OR LIMITATION OF INCIDENTAL OR CONSEQUENTIAL DAMAGES, SO THE ABOVE LIMITATIONS MAY NOT APPLY TO YOU. It is the buyer's obligation to test the suitability of the product for an intended use prior to using it. The Limited Warranty extends only to the original purchaser and is not transferable or assignable. Any claim for a defective product must be filed within 30 days of discovery of a problem, and must be submitted with written proof of purchase.

### BOSTIK HOTLINE

**Smart help**  
**1-800-726-7845**

#### Bostik, Inc.

11320 W. Watertown Plank Road  
Wauwatosa, WI 53226

[www.bostik.com/us](http://www.bostik.com/us)

