



# Safety Data Sheet

G64130 BBWFA  
Bostiks Best Wood Floor Adh.

Revision Date 05-May-2017  
Supersedes Date: 18-Oct-2016  
Version 4

## Section 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

### 1.1. Product Identifier

**Product Name** Bostiks Best Wood Floor Adh.  
**Product Code** G64130 BBWFA  
**Product(s) Covered** See section 16 for more information

### 1.2. Relevant Identified Uses of the Substance or Mixture and Uses Advised Against

**Recommended use** Adhesives, sealants.  
**Uses Advised Against** No information available

### 1.3. Details of the Supplier of the Safety Data Sheet

#### Responsible Party

Bostik Inc.  
11320 W. Watertown Plank Road  
Wauwatosa, Wisconsin 53226 USA  
Phone: +1 (800) 843-0844 (Domestic Toll Free)  
Phone: +1 (414) 774-2250 (International)  
Fax: +1 (414) 774-8075

E-mail msds@bostik-us.com

### 1.4. Emergency Telephone Number

Telephone: 1-800-227-0332  
(Outside U.S.) 1-703-527-3887

## Section 2: HAZARD IDENTIFICATION

### 2.1. Classification of the Substance or Mixture

Respiratory sensitization	Category 1
Skin sensitization	Category 1
Reproductive Toxicity	Category 1B
Flammable Liquids	Category 4

### 2.2. Label Elements

#### EMERGENCY OVERVIEW

**DANGER**

#### Hazard statements

May cause allergy or asthma symptoms or breathing difficulties if inhaled  
May cause an allergic skin reaction  
May damage fertility or the unborn child  
Combustible liquid

# Safety Data Sheet

G64130 BBWFA  
Bostiks Best Wood Floor Adh.

Revision Date 05-May-2017  
Supersedes Date: 18-Oct-2016  
Version 4



**Appearance** Paste **Physical State** Liquid **Odor** No information available

## Precautionary Statements - Prevention

Obtain special instructions before use  
Do not handle until all safety precautions have been read and understood  
Use personal protective equipment as required  
Avoid breathing dust/fume/gas/mist/vapors/spray  
In case of inadequate ventilation wear respiratory protection  
Contaminated work clothing should not be allowed out of the workplace  
Wear protective gloves  
Keep away from heat/sparks/open flames/hot surfaces. — No smoking

## Precautionary Statements - Response

IF exposed or concerned: Get medical advice/attention  
Specific treatment (see first aid measures on this label)  
IF ON SKIN: Wash with plenty of soap and water. If skin irritation or rash occurs: Get medical advice/attention. Wash contaminated clothing before reuse.  
IF INHALED: If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing. If experiencing respiratory symptoms: Call a POISON CENTER or doctor/physician.  
In case of fire: Use CO<sub>2</sub>, dry chemical, or foam to extinguish.

## Precautionary Statements - Storage

Store locked up  
Store in a well-ventilated place. Keep cool

## Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

## Hazards Not Otherwise Classified (HNOC)

Not applicable

## Unknown acute toxicity

27% of the mixture consists of ingredient(s) of unknown toxicity

## 2.3. Other Information

Causes mild skin irritation.

## Section 3: COMPOSITION/INFORMATION ON INGREDIENTS

### 3.1 Substances

Mixture

### 3.2 Mixtures

Chemical Name	CAS No.	Weight-%
Limestone	1317-65-3	30 - 60
Naphtha, petroleum, heavy alkylate	64741-65-7	3 - 7
Benzenesulfonyl isocyanate, 4-methyl-	4083-64-1	0.1 - 1

# Safety Data Sheet

G64130 BBWFA  
Bostiks Best Wood Floor Adh.

Revision Date 05-May-2017  
Supersedes Date: 18-Oct-2016  
Version 4

Dibutyltin dilaurate	77-58-7	0.1 - 1
Quartz	14808-60-7	0.1 - 1

*The exact percentage (concentration) of composition has been withheld as a trade secret.*

## Section 4: FIRST AID MEASURES

### 4.1. Description of First Aid Measures

<b>General Advice</b>	Remove and isolate contaminated clothing and shoes. Call a POISON CENTER or doctor/physician.
<b>Eye contact</b>	In case of contact with substance, immediately flush skin or eyes with running water for at least 20 minutes. If eye irritation persists: Get medical advice/attention.
<b>Skin Contact</b>	Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes. Wash contaminated clothing before reuse. May cause sensitization by skin contact. In the case of skin irritation or allergic reactions see a physician.
<b>Inhalation</b>	Move victim to fresh air. Administer oxygen if breathing is difficult. If breathing is irregular or stopped, administer artificial respiration.
<b>Ingestion</b>	Clean mouth with water and drink afterwards plenty of water. Never give anything by mouth to an unconscious person. Do NOT induce vomiting. If symptoms persist, call a physician.
<b>Self-protection of the First Aider</b>	Ensure that medical personnel are aware of the material(s) involved and take precautions to protect themselves.

### 4.2. Most Important Symptoms and Effects, Both Acute and Delayed

**Symptoms** No information available.

### 4.3. Indication of Any Immediate Medical Attention and Special Treatment Needed

**Note to physicians** May cause sensitization by inhalation and skin contact.

### 4.4. Reference to Other Sections

**Reference to Other Sections** Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION  
Section 11: TOXICOLOGY INFORMATION

## Section 5: FIRE-FIGHTING MEASURES

### 5.1. Extinguishing Media

#### **Suitable Extinguishing Media**

Dry chemical, CO<sub>2</sub>, water spray or regular foam. Move containers from fire area if you can do it without risk. Water spray, fog or regular foam. Use water spray or fog; do not use straight streams.

#### **Unsuitable Extinguishing Media**

CAUTION: All these products have a very low flash point. Use of water spray when fighting fire may be inefficient.

### 5.2. Special Hazards Arising from the Substance or Mixture

#### **Specific Hazards Arising from the Chemical**

Vapors may form explosive mixtures with air. Vapors may travel to source of ignition and flash back. Most vapors are heavier than air. They will spread along ground and collect in low or confined areas (sewers, basements, tanks). Vapor explosion hazard indoors, outdoors or in sewers. Runoff to sewer may create fire or explosion hazard. May cause sensitization by inhalation and skin

# Safety Data Sheet

G64130 BBWFA  
Bostiks Best Wood Floor Adh.

Revision Date 05-May-2017  
Supersedes Date: 18-Oct-2016  
Version 4

contact.

## Explosion Data

Sensitivity to Mechanical Impact	None.
Sensitivity to Static Discharge	None.

## 5.3. Advice for Firefighters

### Protective Equipment and Precautions for Firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

## Section 6: ACCIDENTAL RELEASE MEASURES

### 6.1. Personal Precautions, Protective Equipment and Emergency Procedures

#### Personal Precautions

Use personal protective equipment as required. ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). All equipment used when handling the product must be grounded. Do not touch or walk through spilled material. Stop leak if you can do it without risk.

#### Other Information

Water spray may reduce vapor; but may not prevent ignition in closed spaces.

### 6.2. Environmental Precautions

#### Environmental Precautions

Prevent entry into waterways, sewers, basements or confined areas. See Section 12 for additional Ecological Information.

### 6.3. Methods and Material for Containment and Cleaning up

#### Methods for Containment

Dike far ahead of liquid spill for later disposal. A vapor suppressing foam may be used to reduce vapors. Absorb or cover with dry earth, sand or other non-combustible material and transfer to containers. Protect from moisture.

#### Methods for Cleaning up

Use personal protective equipment as required. Soak up with inert absorbent material. Use clean non-sparking tools to collect absorbed material. Pick up and transfer to properly labeled containers. Clean contaminated surface thoroughly.

### 6.4. Reference to other sections

#### Reference to Other Sections

Section 7: HANDLING AND STORAGE  
Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION  
Section 13: DISPOSAL CONSIDERATIONS

## Section 7: HANDLING AND STORAGE

### 7.1. Precautions for Safe Handling

#### Advice on Safe Handling

Use personal protective equipment as required. Handle in accordance with good industrial hygiene and safety practice. Avoid contact with skin, eyes or clothing. Wash contaminated clothing before reuse. Do not breathe dust/fume/gas/mist/vapors/spray. Ensure adequate ventilation, especially in confined areas. Use with local exhaust ventilation. All equipment used when handling the product must be grounded. Keep away from heat/sparks/open flames/hot surfaces. — No smoking. Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapors).

### 7.2. Conditions for Safe Storage, including any Incompatibilities

# Safety Data Sheet

G64130 BBWFA  
Bostiks Best Wood Floor Adh.

Revision Date 05-May-2017  
Supersedes Date: 18-Oct-2016  
Version 4

**Storage Conditions** Keep in properly labeled containers. Keep out of the reach of children. Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity). Keep containers tightly closed in a cool, well-ventilated place. Protect from direct contact with water or excessive moisture.

**Incompatible Materials** Water. Alcohols. Strong bases. Strong oxidizing agents. Finely powdered metals.

**7.3. Specific End Use(s)**

**Other Information** No information available.

**7.4. References to Other Sections**

**Reference to Other Sections** Section 13: DISPOSAL CONSIDERATIONS  
Section 10: STABILITY AND REACTIVITY

**Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION**

**8.1. Control Parameters**

**Exposure Guidelines** . As Quartz (14808-60-7) is inextricably bound in the polymer matrix, it is not expected to be available as an airborne hazard (dust, mist, or spray) under normal condition of uses. As Limestone CAS 1317-65-3 is inextricably bound in the polymer matrix, it is not expected to be available as an airborne hazard (dust, mist, or spray) under normal condition of uses.

Chemical Name	ACGIH TLV	NIOSH IDLH	OSHA PEL	Mexico
Limestone 1317-65-3	-	TWA: 10 mg/m <sup>3</sup> total dust TWA: 5 mg/m <sup>3</sup> respirable dust	TWA: 15 mg/m <sup>3</sup> total dust TWA: 5 mg/m <sup>3</sup> respirable fraction	TWA: 10 mg/m <sup>3</sup> STEL: 20 mg/m <sup>3</sup>
Dibutyltin dilaurate 77-58-7	STEL: 0.2 mg/m <sup>3</sup> Sn TWA: 0.1 mg/m <sup>3</sup> Sn S*	IDLH: 25 mg/m <sup>3</sup> Sn TWA: 0.1 mg/m <sup>3</sup> except Cyhexatin Sn	TWA: 0.1 mg/m <sup>3</sup> Sn	TWA: 0.1 mg/m <sup>3</sup> STEL: 0.2 mg/m <sup>3</sup>
Quartz 14808-60-7	TWA: 0.025 mg/m <sup>3</sup> respirable particulate matter	IDLH: 50 mg/m <sup>3</sup> respirable dust TWA: 0.05 mg/m <sup>3</sup> respirable dust	TWA: 50 µg/m <sup>3</sup> TWA: 50 µg/m <sup>3</sup> excludes construction work, agricultural operations, and exposures that result from the processing of sorptive clays : (250)/(%SiO <sub>2</sub> + 5) mppcf TWA respirable fraction : (10)/(%SiO <sub>2</sub> + 2) mg/m <sup>3</sup> TWA respirable fraction	TWA: 0.1 mg/m <sup>3</sup>

Chemical Name	Argentina	Brazil	Chile	Venezuela
Limestone 1317-65-3	TWA: 10 mg/m <sup>3</sup>	-	TWA: 8 mg/m <sup>3</sup>	-
Dibutyltin dilaurate 77-58-7	TWA: 0.1 mg/m <sup>3</sup> Skin STEL: 0.2 mg/m <sup>3</sup>	-	TWA: 0.08 mg/m <sup>3</sup> Skin	Skin STEL: 0.2 mg/m <sup>3</sup> TWA: 0.1 mg/m <sup>3</sup>
Quartz 14808-60-7	TWA: 0.05 mg/m <sup>3</sup>	-	TWA: 0.08 mg/m <sup>3</sup>	TWA: 0.025 mg/m <sup>3</sup>

**8.2. Exposure Controls**

**Engineering Controls** Showers  
Eyewash stations  
Ventilation systems.

# Safety Data Sheet

G64130 BBWFA  
Bostiks Best Wood Floor Adh.

Revision Date 05-May-2017  
Supersedes Date: 18-Oct-2016  
Version 4

## Personal protective equipment [PPE]

<b>Eye/Face Protection</b>	Tight sealing safety goggles.
<b>Skin and Body Protection</b>	Wear suitable chemical resistant gloves. The selection of suitable gloves does not only depend on the material, but also on further marks of quality and various manufacturers.
<b>Respiratory Protection</b>	If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved respiratory protection should be worn. Positive-pressure supplied air respirators may be required for high airborne contaminant concentrations. Respiratory protection must be provided in accordance with current local regulations.
<b>General Hygiene Considerations</b>	Use personal protective equipment as required. Handle in accordance with good industrial hygiene and safety practice. When using do not eat, drink or smoke. Avoid contact with skin, eyes or clothing. Wash face, hands and any exposed skin thoroughly after handling. Wash contaminated clothing before reuse. Regular cleaning of equipment, work area and clothing is recommended.

## Section 9: PHYSICAL AND CHEMICAL PROPERTIES

### 9.1. Information on Basic Physical and Chemical Properties

<b>Physical State</b>	Liquid
<b>Appearance</b>	Paste
<b>Color</b>	Amber
<b>Odor</b>	No information available
<b>Odor Threshold</b>	No information available

<u>Property</u>	<u>Values</u>	<u>Remarks • Method</u>
pH	No information available	
Melting Point/Freezing Point	No information available	
Boiling Point	> 172 °C / 341.6 °F	
Flash Point	> 61.1 °C / > 142 °F	
Evaporation Rate	No information available	
Flammability (solid, gas)	No information available	Not applicable for liquids
Flammability Limit in Air		
Upper Flammability Limit	No information available	
Lower Flammability Limit	No information available	
Vapor Pressure	No information available	
Vapor Density	No information available	
Relative Density	No information available	
Water Solubility	No information available	
Solubility in Other Solvents		
Partition Coefficient	No information available	
Autoignition Temperature	No information available	
Decomposition Temperature	No information available	
Kinematic Viscosity	No information available	
Dynamic Viscosity	No information available	
Explosive Properties	No information available	
Oxidizing Properties	No information available	

### 9.2. Other Information

<b>Softening Point</b>	No information available
<b>Molecular Weight</b>	No information available
<b>Solvent Content (%)</b>	No information available
<b>Solid Content (%)</b>	93.0
<b>Density</b>	1.508 g/cm <sup>3</sup>
<b>VOC</b>	20 g/L

## Section 10: STABILITY AND REACTIVITY

# Safety Data Sheet

G64130 BBWFA  
Bostiks Best Wood Floor Adh.

Revision Date 05-May-2017  
Supersedes Date: 18-Oct-2016  
Version 4

## 10.1. Reactivity

None under normal use conditions.

## 10.2. Chemical Stability

Stable under recommended storage conditions.

## 10.3. Possibility of Hazardous Reactions

None under normal processing.

**Hazardous Polymerization** Hazardous polymerization may occur.

## 10.4. Conditions to Avoid

Heat, flames and sparks. Keep from any possible contact with water. Extremes of temperature and direct sunlight. Storage near to reactive materials. Protect from moisture.

## 10.5. Incompatible Materials

Water. Alcohols. Strong bases. Strong oxidizing agents. Finely powdered metals.

## 10.6. Hazardous Decomposition Products

Carbon monoxide. Carbon dioxide (CO<sub>2</sub>). Nitrogen oxides (NO<sub>x</sub>). Hydrogen cyanide. Thermal decomposition can lead to release of irritating and toxic gases and vapors.

## **Section 11: TOXICOLOGY INFORMATION**

### 11.1. Information on Toxicological Effects

<b>Product Information</b>	No Data Available
<b>Inhalation</b>	No Data Available.
<b>Eye contact</b>	No Data Available.
<b>Skin Contact</b>	No Data Available.
<b>Ingestion</b>	No Data Available.

### **Component Information**

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
Limestone 1317-65-3	>5000 mg/kg (rat)	-	-
Naphtha, petroleum, heavy alkylate 64741-65-7	> 7000 mg/kg ( Rat )	> 2000 mg/kg ( Rabbit )	> 5.04 mg/L ( Rat ) 4 h
Benzenesulfonyl isocyanate, 4-methyl- 4083-64-1	= 2234 mg/kg ( Rat )	-	> 640 ppm ( Rat ) 1 h
Dibutyltin dilaurate 77-58-7	= 2071 mg/kg ( Rat )	> 2000 mg/kg ( Rat )	-
Quartz 14808-60-7	>2000 mg/kg ( Rat )	-	-

### Delayed and Immediate Effects as well as Chronic Effects from Short and Long-term Exposure

<b>Symptoms</b>	No information available.
<b>Skin Corrosion/Irritation</b>	No information available.
<b>Serious Eye Damage/Eye Irritation</b>	No information available.
<b>Irritation</b>	No information available.

# Safety Data Sheet

G64130 BBWFA  
Bostiks Best Wood Floor Adh.

Revision Date 05-May-2017  
Supersedes Date: 18-Oct-2016  
Version 4

<b>Corrosivity</b>	No information available.
<b>Sensitization</b>	No information available.
<b>Germ Cell Mutagenicity</b>	No information available.
<b>Reproductive Toxicity</b>	No information available.
<b>Developmental Toxicity</b>	No information available.
<b>Teratogenicity</b>	No information available.
<b>STOT - Single Exposure</b>	No information available.
<b>STOT - Repeated Exposure</b>	No information available.
<b>Chronic Toxicity</b>	Repeated contact may cause allergic reactions in very susceptible persons. Avoid repeated exposure. Repeated or prolonged exposure may cause central nervous system damage. Repeated or prolonged contact causes sensitization, asthma and eczemas.
<b>Target Organ Effects</b>	Eyes, Respiratory system, Skin, Central nervous system.
<b>Aspiration Hazard</b>	No information available.
<b>Carcinogenicity</b>	The table below indicates whether each agency has listed any ingredient as a carcinogen. As Quartz (14808-60-7) is inextricably bound in the polymer matrix, it is not expected to be available as an airborne hazard (dust, mist, or spray) under normal condition of uses.

Chemical Name	ACGIH	IARC	NTP	OSHA
Quartz 14808-60-7	A2	Group 1	Known	X

ACGIH (American Conference of Governmental Industrial Hygienists)  
A2 - Suspected Human Carcinogen  
IARC (International Agency for Research on Cancer)  
Group 1 - Carcinogenic to Humans  
NTP (National Toxicology Program)  
Known - Known Carcinogen  
OSHA (Occupational Safety and Health Administration of the US Department of Labor)  
X - Present

## Section 12: ECOLOGICAL INFORMATION

### 12.1. Toxicity

No information available

Chemical Name	Algae/Aquatic Plants	Fish	Toxicity to Microorganisms	Crustacea
Limestone 1317-65-3	CE50 (72h) >200mg/L Algae (Desmodesmus subspicatus)	CL50 (96h) >10000mg/L Fish (Oncorhynchus mykiss)		CE50 (48h) >1000 mg/L Daphnia Magna
Naphtha, petroleum, heavy alkylate 64741-65-7	EC50 72 h = 30000 mg/L (Pseudokirchneriella subcapitata)			LC50 48 h = 2 mg/L (Mysidopsis bahia )
Dibutyltin dilaurate 77-58-7		LC50 48 h = 2 mg/L (Oryzias latipes )		

### 12.2. Persistence and Degradability

No information available.

### 12.3. Bioaccumulative Potential

No information available.

### 12.4. Mobility in Soil

No information available.



# Safety Data Sheet

G64130 BBWFA  
Bostiks Best Wood Floor Adh.

Revision Date 05-May-2017  
Supersedes Date: 18-Oct-2016  
Version 4

## 12.5 Other adverse effects

No information available

## Section 13: DISPOSAL CONSIDERATIONS

### 13.1. Waste Treatment Methods

**Disposal of Wastes** It is the responsibility of the waste generator to determine the toxicity and physical properties of the material generated to determine the proper waste identification and disposal methods in compliance with applicable regulations

**Contaminated Packaging** Dispose of in accordance with federal, state and local regulations

## Section 14: TRANSPORTATION INFORMATION

**Note:** 49 CFR 173.150(f)(2) "The requirements in this subchapter do not apply to a material classed as a combustible liquid in a non-bulk packaging unless the combustible liquid is a hazardous substance, a hazardous waste, or a marine pollutant."

### DOT

<b>UN/ID No</b>	NA1993
<b>Hazard Class</b>	Combustible liquid
<b>Packing Group</b>	III
<b>Special Provisions</b>	IB3, T1, T4, TP1
<b>Description</b>	NA1993, Combustible liquid, n.o.s. (Naphtha, petroleum, heavy alkylate), Combustible liquid, III,
<b>Emergency Response Guide Number</b>	128

**IATA** Not regulated

**IMDG** Not regulated

## Section 15: REGULATORY INFORMATION

### Global Inventories

<b>TSCA</b>	Listed
<b>DSL</b>	Listed

### Legend:

**TSCA** - United States Toxic Substances Control Act Section 8(b) Inventory

**DSL** - Canadian Domestic Substances List

**Listed** - The components of this product are either listed or exempt from listing on inventory.

**Not Listed** - One or more components of this product are not listed on inventory.

### Canada

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the MSDS contains all the information required by the CPR

### WHMIS Hazard Class

B3 - Combustible liquid

D2A - Very toxic materials

# Safety Data Sheet

G64130 BBWFA  
Bostiks Best Wood Floor Adh.

Revision Date 05-May-2017  
Supersedes Date: 18-Oct-2016  
Version 4



## United States of America

### SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product does not contain any chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

### SARA 311/312 Hazard Categories

Acute Health Hazard	yes
Chronic Health Hazard	yes
Fire Hazard	yes
Sudden release of pressure hazard	No
Reactive Hazard	No

### California Proposition 65

This product contains one or more of the substances listed on Proposition 65 at or above 0.01 wt. %

Chemical Name	CAS No.
1,2-Benzenedicarboxylic acid, di-C9-11-branched alkyl esters, C10-rich	68515-49-1
Quartz	14808-60-7
N-(trichloromethylthio)phthalimide	133-07-3

## Europe

### **Restrictions of Use of Hazardous Substances (RoHS) Directive 2011/65/EU**

This product does not contain Lead (7439-92-1), Cadmium (7440-43-9), Mercury (7439-97-6), Hexavalent chromium (7440-47-3), Polybrominated biphenyls (PBB), and Polybrominated diphenyl ethers (PBDE) above the regulated limit mentioned in this regulation.

### **EU-REACH (1907/2006) - Candidate List of Substances of Very High Concern (SVHC) for Authorization in accordance with Article 59**

This product does not contain candidate substances of very high concern at a concentration  $\geq 0.1\%$  (Regulation (EC) No. 1907/2006 (REACH), Article 59)

## **Section 16: OTHER INFORMATION**

### **Product(s) Covered**

A38910	BEST FCt10.1OZ/C24
A38921	BEST FCt28OZ/C12
A39000	BEST FCt10.1OZ/C12
G64130-BU	BEST MP5GL/P36
G64130-BUC	BEST Ca MP5GL/P24
G64140-95L	BEST MD52GL(654LB)/P3
G64140-DZ	BEST MP5GL/P36
G64140-DZC	BEST Ca MP5GL/P36

**HMIS** Health Hazards 2\* Flammability 2 Physical Hazards 0 Personal Protection X

### **Key or Legend to Abbreviations and Acronyms Used in the Safety Data Sheet**

No information available

### **Key Literature References and Sources for Data**

# Safety Data Sheet

**G64130 BBWFA**  
**Bostiks Best Wood Floor Adh.**

**Revision Date** 05-May-2017  
**Supersedes Date:** 18-Oct-2016  
**Version** 4

---

No information available

<b>Prepared By</b>	Product Safety & Regulatory Affairs
<b>Revision Date</b>	05-May-2017
<b>Revision Note</b>	SDS sections updated, 2, 3, 4, 7, 8, 11.
<b>Training Advice</b>	No information available
<b>Additional information</b>	No information available

## **Disclaimer**

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

**End of Safety Data Sheet**