

GoBoard® Pro Sealant

Version 2.1

Revision Date 04/23/2021

Print Date 01/04/2022

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Trade name : GoBoard® Pro Sealant

Manufacturer or supplier's details

Company : Johns Manville

Address : P.O. Box 5108
Denver, CO USA 80127

Telephone : +1-303-978-2000

Emergency telephone number : 24-Hour Number: +1-800-424-9300 (CHEMTREC)

Company : Johns Manville Canada Inc.

Address : 5301 42 Avenue
Innisfail, AB Canada T4G 1A2

Telephone : +1-303-978-2000

Emergency telephone number : 24-Hour Number: +1-800-424-9300 (CHEMTREC)

Recommended use of the chemical and restrictions on use

Recommended use : Adhesives and/or sealants

Prepared by : productsafety@jm.com

SECTION 2. HAZARDS IDENTIFICATION**GHS classification in accordance with 29 CFR 1910.1200 (OSHA HCS 2012) and the Hazardous Products Regulations (WHMIS 2015)**

Skin irritation : Category 2

Eye irritation : Category 2A

Skin sensitisation : Category 1

Reproductive toxicity : Category 1B

GHS label elements

Hazard pictograms :



Signal word : Danger

Hazard statements : H315 Causes skin irritation.
H317 May cause an allergic skin reaction.
H319 Causes serious eye irritation.
H360 May damage fertility or the unborn child.Precautionary statements : **Prevention:**
P201 Obtain special instructions before use.

GoBoard® Pro Sealant

Version 2.1

Revision Date 04/23/2021

Print Date 01/04/2022

P202 Do not handle until all safety precautions have been read and understood.

P261 Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray.

P264 Wash skin thoroughly after handling.

P272 Contaminated work clothing must not be allowed out of the workplace.

P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.

Response:

P302 + P352 IF ON SKIN: Wash with plenty of soap and water.

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P308 + P313 IF exposed or concerned: Get medical advice/ attention.

P333 + P313 If skin irritation or rash occurs: Get medical advice/ attention.

P337 + P313 If eye irritation persists: Get medical advice/ attention.

P362 Take off contaminated clothing and wash before reuse.

Storage:

P405 Store locked up.

Disposal:

P501 Dispose of contents/container to an approved facility in accordance with local, regional, national and international regulations.

Other hazards

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical nature

Adhesives and/or sealants

Hazardous components

Chemical name	CAS-No.	Concentration (%)
calcium carbonate	471-34-1	>= 30 - < 60
trimethoxyvinylsilane	2768-02-7	>= 1 - < 5
titanium dioxide	13463-67-7	>= 1 - < 5
3-aminopropyltriethoxysilane	919-30-2	>= 1 - < 5
dibutylbis(pentane-2,4-dionato-O,O')tin	22673-19-4	>= 0.1 - < 1

Actual concentration or concentration range is withheld as a trade secret

SECTION 4. FIRST AID MEASURES

General advice : Move out of dangerous area.
 Show this safety data sheet to the doctor in attendance.
 Do not leave the victim unattended.

If inhaled : Remove person to fresh air. If signs/symptoms continue, get medical attention.

GoBoard® Pro Sealant

Version 2.1

Revision Date 04/23/2021

Print Date 01/04/2022

In case of skin contact	:	In case of contact, immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. Call a physician if irritation develops or persists.
In case of eye contact	:	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If easy to do, remove contact lens, if worn. Protect unharmed eye. If eye irritation persists, consult a specialist.
If swallowed	:	DO NOT induce vomiting unless directed to do so by a physician or poison control center. Gently wipe or rinse the inside of the mouth with water. Never give anything by mouth to an unconscious person. Get medical attention immediately. If breathing is irregular or stopped, administer artificial respiration.
Most important symptoms and effects, both acute and delayed	:	Causes skin irritation. May cause an allergic skin reaction. Causes serious eye irritation. May damage fertility or the unborn child.

SECTION 5. FIREFIGHTING MEASURES

Suitable extinguishing media	:	Carbon dioxide (CO ₂) Dry powder Water spray Alcohol-resistant foam
Unsuitable extinguishing media	:	High volume water jet
Hazardous combustion products	:	carbon oxides Silicon oxides titanium/titanium oxides nitrogen oxides
Specific extinguishing methods	:	Use water spray to cool unopened containers.
Further information	:	Standard procedure for chemical fires. Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.
Special protective equipment for firefighters	:	Wear self-contained breathing apparatus for firefighting if necessary.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions,	:	Use personal protective equipment.
-----------------------	---	------------------------------------

GoBoard® Pro Sealant

Version 2.1

Revision Date 04/23/2021

Print Date 01/04/2022

protective equipment and
emergency procedures

Environmental precautions : Prevent product from entering drains.
Prevent further leakage or spillage if safe to do so.
If the product contaminates rivers and lakes or drains inform
respective authorities.

Methods and materials for
containment and cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel,
acid binder, universal binder, sawdust).
Keep in suitable, closed containers for disposal.

SECTION 7. HANDLING AND STORAGE

Advice on protection against
fire and explosion : Normal measures for preventive fire protection.

Advice on safe handling : Do not breathe vapours/dust.
Avoid exposure - obtain special instructions before use.
Avoid contact with skin and eyes.
For personal protection see section 8.
Smoking, eating and drinking should be prohibited in the
application area.
Persons susceptible to skin sensitisation problems or asthma,
allergies, chronic or recurrent respiratory disease should not
be employed in any process in which this mixture is being
used.

Conditions for safe storage : Keep container tightly closed in a dry and well-ventilated
place.
Observe label precautions.

Storage period : 18 Months

Further information on
storage stability : Keep in a dry, cool place.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
titanium dioxide	13463-67-7	TWA (total dust)	15 mg/m ³	OSHA
		TWA	10 mg/m ³ (Titanium dioxide)	ACGIH
dibutylbis(pentane-2,4-dionato- O ₂ O')tin	22673-19-4	TWA	0.1 mg/m ³ (Tin)	OSHA
		TWA	0.1 mg/m ³ (Tin)	ACGIH
		STEL	0.2 mg/m ³	ACGIH

GoBoard® Pro Sealant

Version 2.1

Revision Date 04/23/2021

Print Date 01/04/2022

			(Tin)	
		TWA	0.1 mg/m ³ (Tin)	OSHA
		TWA	0.1 mg/m ³ (Tin)	NIOSH REL
methanol	67-56-1	TWA	200 ppm	ACGIH
		STEL	250 ppm	ACGIH
		TWA	200 ppm 260 mg/m ³	NIOSH REL
		ST	250 ppm 325 mg/m ³	NIOSH REL
		TWA	200 ppm 260 mg/m ³	OSHA

Personal protective equipment

Respiratory protection : General and local exhaust ventilation is recommended to maintain vapor exposures below recommended limits. Where concentrations are above recommended limits or are unknown, appropriate respiratory protection should be worn. Follow OSHA respirator regulations (29 CFR 1910.134) and use NIOSH/MSHA approved respirators. Protection provided by air purifying respirators against exposure to any hazardous chemical is limited. Use a positive pressure air supplied respirator if there is any potential for uncontrolled release, exposure levels are unknown, or any other circumstance where air purifying respirators may not provide adequate protection.

Hand protection
Material : Rubber gloves

Remarks : Take note of the information given by the producer concerning permeability and break through times, and of special workplace conditions (mechanical strain, duration of contact).

Eye protection : Wear safety glasses with side shields or goggles.
Wear face-shield and protective suit for abnormal processing problems.

Skin and body protection : Wear protective clothing, such as long-sleeved shirts and pants.
Choose body protection according to the amount and concentration of the dangerous substance at the work place.

Hygiene measures : Handle in accordance with good industrial hygiene and safety practice.
When using do not eat or drink.
When using do not smoke.
Wash hands before breaks and at the end of workday.
Written instructions for handling must be available at the work place.

GoBoard® Pro Sealant

Version 2.1

Revision Date 04/23/2021

Print Date 01/04/2022

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	: paste
Colour	: white
Odour	: slight
Odour Threshold	: No data available
pH	: Not applicable
Melting point/freezing point	: not determined
Initial boiling point and boiling range	: ≥ 288 °C
Flash point	: > 200 °C Method: Cleveland open cup
Evaporation rate	: No data available
Flammability (solid, gas)	: No data available
Upper explosion limit	: No data available
Lower explosion limit	: No data available
Vapour pressure	: > 0.0000000 hPa (20 °C)
Relative vapour density	: No data available
Relative density	: No data available
Density	: 1.5 g/cm ³ (20 °C)
Solubility(ies)	
Water solubility	: immiscible
Solubility in other solvents	: No data available
Partition coefficient: n-octanol/water	: No data available
Auto-ignition temperature	: ≥ 305 °C
Thermal decomposition	: No data available
Viscosity	
Viscosity, dynamic	: 600,000 mPa.s (23 °C)
Viscosity, kinematic	: No data available

GoBoard® Pro Sealant

Version 2.1

Revision Date 04/23/2021

Print Date 01/04/2022

SECTION 10. STABILITY AND REACTIVITY

Reactivity	:	Stable at normal ambient temperature and pressure.
Chemical stability	:	No decomposition if stored and applied as directed.
Possibility of hazardous reactions	:	Methanol is given off during processing and by reaction with water. No decomposition if stored and applied as directed.
Conditions to avoid	:	Exposure to moisture
Incompatible materials	:	Water

Hazardous decomposition products

Contact with water or humid air : Methanol

SECTION 11. TOXICOLOGICAL INFORMATION**Acute toxicity****Product:**

Acute oral toxicity	:	Acute toxicity estimate : > 5,000 mg/kg Method: Calculation method
Acute inhalation toxicity	:	Acute toxicity estimate : > 200 mg/l Exposure time: 4 h Test atmosphere: vapour Method: Calculation method
Acute dermal toxicity	:	Acute toxicity estimate : > 5,000 mg/kg Method: Calculation method

Acute toxicity**Components:****calcium carbonate:**

Acute oral toxicity	:	LD50 (Rat, female): > 2,000 mg/kg Method: OECD Test Guideline 420 GLP: yes
Acute inhalation toxicity	:	LC50 (Rat, male and female): > 3 mg/l Exposure time: 4 h Test atmosphere: dust/mist Method: OECD Test Guideline 403 GLP: yes Assessment: The substance or mixture has no acute inhalation toxicity
Acute dermal toxicity	:	LD50 (Rat, male and female): > 2,000 mg/kg Method: OECD Test Guideline 402 GLP: yes

GoBoard® Pro Sealant

Version 2.1

Revision Date 04/23/2021

Print Date 01/04/2022

Acute toxicity
trimethoxyvinylsilane:

- Acute oral toxicity : LD50 Oral (Rat, male): 7,120 mg/kg
 Method: OECD Test Guideline 401
- Acute inhalation toxicity : LC50 (Rat, male and female): 16.8 mg/l
 Exposure time: 4 h
 Test atmosphere: vapour
 Method: OECD Test Guideline 403

- Acute dermal toxicity : LD50 (Rabbit): 3,600 - 4,000 mg/kg
 Method: OECD Test Guideline 402

Acute toxicity
titanium dioxide:

- Acute oral toxicity : LD50 (Rat, male and female): > 2,000 mg/kg
- Acute inhalation toxicity : LC50 (Rat, male and female): > 5.09 mg/l
 Exposure time: 4 h
 Test atmosphere: dust/mist
 Method: OECD Test Guideline 403
- Acute dermal toxicity : Method: Expert judgement
 Assessment: The substance or mixture has no acute dermal toxicity

Acute toxicity
3-aminopropyltriethoxysilane:

- Acute oral toxicity : LD50 (Rat, female): 1,490 mg/kg
- Acute inhalation toxicity : LC50 (Rat, male): > 5 ppm
 Exposure time: 6 h
 Test atmosphere: vapour
 Method: OECD Test Guideline 403
 Assessment: The substance or mixture has no acute inhalation toxicity
- Acute dermal toxicity : LD50 (Rabbit, male and female): 4,080 mg/kg

Acute toxicity
dibutylbis(pentane-2,4-dionato-O,O')tin:

- Acute oral toxicity : LD50 (Rat, female): 1,864 mg/kg
 Method: OECD Test Guideline 401
- Acute inhalation toxicity : Assessment: The substance or mixture has no acute inhalation toxicity
 Remarks: No data available
- Acute dermal toxicity : LD50 (Rat, male and female): > 2,000 mg/kg
 Method: OECD Test Guideline 402

GoBoard® Pro Sealant

Version 2.1

Revision Date 04/23/2021

Print Date 01/04/2022

Skin corrosion/irritation**Components:****3-aminopropyltriethoxysilane:**

Species: Rabbit

Exposure time: 1 h

Method: OECD Test Guideline 404

Result: Corrosive after 3 minutes to 1 hour of exposure

Skin corrosion/irritation**dibutylbis(pentane-2,4-dionato-O,O')tin:**

Species: Rat

Exposure time: 24 h

Method: OECD Test Guideline 402

Result: Corrosive, category 1C - where responses occur after exposures between 1 hour and 4 hours and observations up to 14 days.

Serious eye damage/eye irritation**Components:****3-aminopropyltriethoxysilane:**

Species: Rabbit

Result: Irreversible effects on the eye

Method: OECD Test Guideline 405

Serious eye damage/eye irritation**dibutylbis(pentane-2,4-dionato-O,O')tin:**

Species: Rabbit

Result: Irreversible effects on the eye

Method: in vitro eye irritation test

Remarks: rabbit eye

Respiratory or skin sensitisation**Components:****3-aminopropyltriethoxysilane:**

Test Type: Buehler Test

Exposure routes: Dermal

Species: Guinea pig

Method: OECD Test Guideline 406

Result: May cause sensitisation by skin contact.

Respiratory or skin sensitisation**dibutylbis(pentane-2,4-dionato-O,O')tin:**

Test Type: Maximisation Test

Species: Guinea pig

Assessment: May cause sensitisation by skin contact.

Method: OECD Test Guideline 406

Germ cell mutagenicity**Components:****dibutylbis(pentane-2,4-dionato-O,O')tin:**

GoBoard® Pro Sealant

Version 2.1

Revision Date 04/23/2021

Print Date 01/04/2022

Germ cell mutagenicity-
Assessment : Positive result(s) from in vivo somatic cell mutagenicity tests supported by positive results from in vitro mutagenicity assays or chemical structure activity relationship to known germ cell mutagens

IARC Group 1: Carcinogenic to humans
quartz (SiO₂) 14808-60-7
Group 2B: Possibly carcinogenic to humans
titanium dioxide 13463-67-7

OSHA No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA (29 CFR 1910 Subpart Z, Toxic and Hazardous Substances).

NTP Known to be human carcinogen
quartz (SiO₂) 14808-60-7

Reproductive toxicity
Components:
dibutylbis(pentane-2,4-dionato-O,O')tin:

Reproductive toxicity - Assessment : Clear evidence of adverse effects on sexual function and fertility, and/or on development, based on animal experiments

STOT - single exposure
Components:
dibutylbis(pentane-2,4-dionato-O,O')tin:

Target Organs: thymus gland
Assessment: Causes damage to organs.

STOT - repeated exposure
Components:
dibutylbis(pentane-2,4-dionato-O,O')tin:

Exposure routes: Ingestion
Target Organs: thymus gland
Assessment: Causes damage to organs through prolonged or repeated exposure.

SECTION 12. ECOLOGICAL INFORMATION
Ecotoxicity
Components:
dibutylbis(pentane-2,4-dionato-O,O')tin:

Toxicity to fish : LC50 (Oryzias latipes (Japanese medaka)): > 2 mg/l
Exposure time: 96 h
Test Type: semi-static test

GoBoard® Pro Sealant

Version 2.1

Revision Date 04/23/2021

Print Date 01/04/2022

Method: OECD Test Guideline 203

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 0.0036 mg/l
 Exposure time: 48 h
 Test Type: static test
 Method: OECD Test Guideline 202

Toxicity to algae : EC50 (Desmodesmus subspicatus (green algae)): 2 mg/l
 Exposure time: 72 h
 Test Type: static test
 Method: OECD Test Guideline 201

M-Factor (Acute aquatic toxicity) : 100

Toxicity to microorganisms : EC50 (activated sludge): 190 mg/l
 Exposure time: 3 h
 Test Type: Respiration inhibition
 Method: OECD Test Guideline 209

Persistence and degradability

No data available

Bioaccumulative potential

Components:

trimethoxyvinylsilane:

Partition coefficient: n-octanol/water : log Pow: -2 - -0.82 (20 °C)
 pH: 7

3-aminopropyltriethoxysilane:

Partition coefficient: n-octanol/water : log Pow: 1.7 (20 °C)
 pH: 7

Mobility in soil

No data available

Other adverse effects

Product:

Ozone-Depletion Potential : Regulation: 40 CFR Protection of Environment; Part 82
 Protection of Stratospheric Ozone - CAA Section 602 Class I Substances
 Remarks: This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A + B).

Additional ecological information : Toxic to aquatic life.
 Toxic to aquatic life with long lasting effects.

SECTION 13. DISPOSAL CONSIDERATIONS

GoBoard® Pro Sealant

Version 2.1

Revision Date 04/23/2021

Print Date 01/04/2022

Disposal methods

- Waste from residues : Dispose of contents/container to an approved facility in accordance with local, regional, national and international regulations.
- Contaminated packaging : Dispose of as unused product.

SECTION 14. TRANSPORT INFORMATION**International transport regulations**

Land transport

USDOT: Not classified as a dangerous good under transport regulations

TDG: Not classified as a dangerous good under transport regulations

Sea transport

IMDG: Not classified as a dangerous good under transport regulations

Air transport

IATA/ICAO: Not classified as a dangerous good under transport regulations

SECTION 15. REGULATORY INFORMATION**TSCA list**

TSCA - 5(a) Significant New Use Rule List of Chemicals : No substances are subject to a Significant New Use Rule.

U.S. Toxic Substances Control Act (TSCA) Section 12(b) Export Notification (40 CFR 707, Subpart D) : No substances are subject to TSCA 12(b) export notification requirements.

EPCRA - Emergency Planning and Community Right-to-Know Act**CERCLA Reportable Quantity**

This material does not contain any components with a CERCLA RQ.

SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 311/312 Hazards : Skin corrosion or irritation
Respiratory or skin sensitisation
Reproductive toxicity
Serious eye damage or eye irritation

SARA 302 : This material does not contain any components with a section 302 EHS TPQ.

SARA 313 : This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

Clean Air Act

GoBoard® Pro Sealant

Version 2.1

Revision Date 04/23/2021


Print Date 01/04/2022

This product does not contain any hazardous air pollutants (HAP), as defined by the U.S. Clean Air Act Section 112 (40 CFR 61).

This product does not contain any chemicals listed under the U.S. Clean Air Act Section 112(r) for Accidental Release Prevention (40 CFR 68.130, Subpart F).

This product does not contain any chemicals listed under the U.S. Clean Air Act Section 111 SOCM Intermediate or Final VOC's (40 CFR 60.489).

California Prop. 65

 **WARNING:** This product can expose you to chemicals including methanol, which is/are known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

The components of this product are reported in the following inventories:

TSCA : All substances listed as active on the TSCA inventory

DSL : All components of this product are on the Canadian DSL

SECTION 16. OTHER INFORMATION**Further information**

Revision Date : 04/23/2021

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.