



Husqvarna®



Husqvarna Soff-Cut 2500

The Husqvarna Soff-Cut 2500 self-propelled dry cutting gas saw has a low noise enclosed design and is ideal for medium to heavy-duty commercial, industrial and paving applications. The 2500 is designed for versatility, ease of use and high production capabilities. Three blade widths can be used, allowing for different joint widths and crack control simultaneously. Features include a 13 hp engine, halogen lighting system, electric remote key start, and a cyclone air cleaner to increase engine longevity.



SOFF-CUT™ TECHNOLOGY

Husqvarna Soff-Cut is a unique patented system for early entry concrete sawing. This technology enables concrete to be cut within the first one or two hours of finishing and before final set. Husqvarna Soff-Cut™ provides the best solution for minimizing the risk of random cracking, and it simplifies the working process, compared to conventional sawing.

Features Husqvarna Soff-Cut 2500

- Self-propelled gas saw with positraction drive, hydrostatic transmission and travel speed indicator.
- Switch-activated electronic adjustable handles.
- Master switch control panel.
- Electronic remote key start and choke.
- High-strength, lightweight aluminium frame.
- 10 amp regulated charging system.
- Switch-activated blade depth control and retractable guide.
- Patented dry-cut diamond blade, anti-ravel skid plate and safety arbor.
- Patented low-noise and low-dust blade block enclosure.

TECHNICAL SPECIFICATION	
Motor manufacturer	Honda
Motor spec	GX390
Max output (As rated by the engine manufacturer)	8.2 kW / 11 hp
Cylinders	1
Number of strokes	4-stroke engine
Cylinder displacement	23.7 cu.inch
Cylinder bore	3.5 inch
Fuel tank volume	1.6 gal.
Starter	Electric
Engine cooling	Air
Number of belts	2
Displacement, l	389 lit
Oil capacity, l	1.1 lit
Output RPM	3200 rpm
Diamond blade, max	10"
Max cutting depth	1.5 inch
Blade depth control	Electric
Blade control	Electric Remote
Blade shaft diameter	1.25 inch
Blade flange	4.25"
Blade shaft RPM	3200 rpm
Axle front	0.75 inch
Rear axle diameter	1 inch
Handle bars	Multi position
Primary wheel size	Outside diameter: 4 Wheel width: 3 Inner bore: 0"
Secondary wheel size	Outside diameter: 8 Wheel width: 3 Inner bore: 0"
Weight	347 lbs
Weight incl. packaging	418 lbs
Product size, LxWxH	76x23x36 inch

