




Husqvarna TS 70

TS 70 is the perfect choice for fast and effective cutting of materials up to 28 inches in length. The optional adjustable stand enables one person to move the TS 70 around the jobsite. With the optional stands the tile saw can easily be positioned to various heights or collapsed with one hand. The quick and easy set up gives you more time for cutting. The water management system minimizes the water use for a clean work area. The machine is equipped with a separate water tank which supplies all water needed and facilitates the slurry sedimentation. Delivered with VARI-CUT™ tile blade.



EASY TRANSPORT

Quick and easy set-up and breakdown mean more time cutting on the job.



CLEAN WORK SPACE

Keeps water and slurry in the cart, not on the tile face like traditional saws, so there is little slurry to wipe off after cutting.



EXCEPTIONAL CUTTING CAPACITY

The cart enables 28" rip cut and cut 20"x20" tiles diagonal.



SEPARATE WATER TANK WITH CAP

Supplies all water needed to the blade and cart. It is stored on cart and does not have to be moved separately.

Features Husqvarna TS 70

- Water is directed to the cart trench or through the blade guard when needed, by a patented Jet Stream Containment System.
- Splash guard
- Flexible sawing

TECHNICAL DATA	
Power output	1,1 kW
Motor rpm	3000 rpm
Voltage	100 - 120 V
Rated current, A	14 A
Phases	1
Current phase cycle	60 Hz
Blade shaft RPM	3000 rpm
Spindle diameter	15,9 mm
Blade diameter	254 mm
Max cutting depth	78 mm
Max cutting length	720 mm
Water tank volume	12,5 lit
Product size, LxWxH	1120x690x590 mm
Weight	58,1 kg
Weight incl. packaging	73,1 kg