

Hole Digging Equipment  
**Hand Held**



**FEATURES**

- Power-FLEX™ operator handles
- Auger-LOK™ for stuck auger removal
- Honda GCV160 engine
- All metal centrifugal clutch
- Precision, spur gear transmission
- 1 inch diameter auger drive connection
- Magura® twist grip throttle control

**262H EPIC™ SERIES TWO MAN HOLE DIGGER**

The 262H EPIC™ Series hand-held Hole Digger offers an uncompromising balance of power, performance and utility in a lightweight, two-man Hole Digger. Its Honda engine directly mounts to a totally enclosed, oil-lubricated transmission for maximum efficiency and is equipped with the convenient Auger-LOK™ for removing stuck augers. Inside, a high capacity, all-metal centrifugal clutch delivers maximum digging power and consistent performance over an extended service life. The exclusive Power-FLEX™ ergonomically engineered composite operator handles maximize control, strength and balance while helping to dampen vibrations. The effects of kickback and fatigue are reduced while increasing overall digging comfort, productivity and jobsite safety. The smooth operating, 4-stroke engine meets applicable emission and noise standards and provides the competitive edge when tackling the tough demands of both industrial and construction related hole digging projects. The 262H Hole Digger is ideally suited for both the home owner and small contractor alike. For use with the 2350 Series earth augers and auger extension.

**SPECIFICATIONS**

<b>Engine</b>	4.4 HP (3.3 Kw), Honda GCV160, 4 Stroke
<b>Starter</b>	Hand rewind
<b>Fuel</b>	Gasoline, unleaded, automotive grade
<b>Transmission</b>	Totally enclosed, spur gear, oil lubricated
<b>Maximum Digging Torque</b>	134 ft lbs (182 N.m)
<b>Nominal Auger Rotation Speed</b>	162 RPM, no load
<b>Auger Drive Connection</b>	1 inch (25.4 mm) round
<b>Available Auger Diameter Range</b>	2 inch (51 mm) to 12 inch (305 mm)
<b>Standard Auger Digging Length</b>	30 inch (762 mm)
<b>Available Auger Extension</b>	15 inch (381 mm), plain-tube type
<b>Weight (less auger)</b>	50 lbs (23 kg)

All specifications are general in nature and are not intended for specific application purposes. General Equipment Company reserves the right to make changes in design, engineering, or specifications and to add improvements or discontinue manufacture at any time without notice or obligation. Consult applicable Operator Manual before utilizing. Refer to OSHA 2207 and/or current revisions for specific safety information. Names depicted are the registered trademarks of their respective owners.