

NORTHROCK
NORTHROCK INDUSTRIES, INC.

PRO 1200 CEILING GRINDER

The Pro 1200 ceiling grinder was designed to easily remove joint lines caused by concrete seepage through forms. Power from either a 1½ HP electric or 4 HP gas motor is transmitted through a heavy duty flexible shaft to a grinding head with a 5/8" - 11 thread. The grinding head is spring-loaded and self-aligning, allowing the grinder to move smoothly over irregular surfaces. The frame is fabricated from strong, light weight aluminium which will not rust when exposed to the elements. Set-up is made simple by a winch system that adjusts the grinder height within seconds. Large diameter tires allow the grinder to roll over work site debris. Our newest feature is a vacuum dust collection system that collects potentially harmful dust at the source, protecting workers' health.



FEATURES & OPTIONS

- Handles ceiling heights from 7' to 12'
- Electric model - 1½ HP Baldor motor
- Gas model - 4 HP Honda engine
- Self-aligning, spring-loaded grinding head
- Welded aluminum frame will not rust
- Rapid winch driven height adjustment
- 12" tires for easy maneuverability
- 5/8" - 11 thread for wheel mount
- Optional dust collection vacuum system



HEAVY DUTY UTILITY GRINDERS



Northrock's line of hand-held grinders are perfect for finishing terrazzo or other concrete applications. They are ideal for grinding, trimming, sanding, and buffing.

CHOICE OF POWER UNITS

Grinders may be driven by a choice of either 115 volt or 220 volt AC power sources running at a choice of 3,450 or 1,725 rpm.

CHOICE OF FRAMES

Northrock power units may be mounted on either skid frames for more stationary applications or on popular rolling tripods for jobs where mobility is required.

CHOICE OF SHAFT

Northrock's field-proven, heavy-duty flexible shafts are available in lengths from 6' to 14' to suit the desired application.

CHOICE OF HANDPIECES

Handpieces for Northrock grinders are available in three configurations - straight and 1:1 or 4:1 right angle heads. A 5/8" - 11 spindle thread is standard. A 3/4" spindle with clamp is available as an option. Right angle heads are available with a water system at the spindle for applications where cooling is desirable.

For an off-the-shelf Northrock grinder custom-configured to suit your needs, contact your local Northrock dealer or Northrock directly.



**BACKPACK VIBRATORS ♦ ELECTRIC VIBRATORS ♦ REBAR ROCKERS ♦ CEILING GRINDERS
HAND-HELD GRINDERS ♦ POWER SCREEDS**